



General Specifications

Power Requirement*	- VDC regulated	6-18 VDC
Current Consumption (at 12VDC)	- Average	31 mA
	- Peak	70 mA
Card Read Range	- Metric	20mm - 40 mm
	- USA	0.8" - 1.6"
Operating Temperature	- Metric	-25°C to +65°C
	- USA	-13°F to +149°F
Relative Humidity	- % max	90%, operating non condensing
Reader Dimensions	- Metric	115mm (L) x 83mm (W) x 26mm (D)
Status LED's	- Colour	Green, Red (ext control to Green)
Audible Tone		Internal & external buzzer control
Colour finish		Charcoal
Certifications		RCM Mark AU/NZ, FCC, CE
IP Rating		IP65
ROHS		Compliant
Face Plate Material		6 mm thick (0.236") Black Acrylic

M2000

* At Reader terminal

A protective custody reader that is highly damage & vandal resistant

The BT835 Series of readers is a flush mount unit designed to be highly damage and vandal resistant. When installed with security screws, it provides the perfect balance of safety and security. The BT835 is often used in forensic and psychiatric hospitals, correctional institutions, immigration detention centres and other applications which require an extremely low profile, highly damage and vandal resistant smart reader.

Available in several models, the BT835 caters for all security requirements large or small and offers a solution for all applications whether driven by budget or functionality.

Model Features

Model	Technology			Authentication Factors		Encode				Encryption				Sector Keys			13.56MHz Credential type and option				Output Protocol			Other						
	Mifare Classic	Mifare Plus	DESfire	Card	Biometric	Keypad	CSN/UID	Sector	Application	Random UID	Diversified Keys	Crypto 1	Mifare Plus	3 DES	AES (optional)	MiPASS 2	MiPASS 3	Customisable	ISO14443A	ISO14443B	Mifare 1K & 4K	Mifare Plus 2K & 4K	DESfire EV1 4K & 8K	Wiegand 32 BIT	Wiegand 26-199 BIT	Encrypted RS485*	Read / Write	Indoor / Outdoor	Tamper option	
BT835-2	✓			✓			✓	✓			✓	✓				✓			✓	✓				✓			✓	✓		
BT835-3	✓			✓			✓	✓			✓	✓						✓	✓	✓				✓	✓	✓	✓	✓	✓	✓
BT835-4		✓	✓				✓	✓	✓		✓	✓	✓			✓			✓	✓			✓				✓	✓		
BT835-6	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

* Requires High Security Module (HSM) AES 128bit encryption

Contact BQT Solutions for more information or a discussion on custom options available, visit our website www.bqtsolutions.com for your nearest office.

[Sep2016] All specifications are subject to change without notice. Contact BQT Solutions to confirm. BQT Solution and miPASS are registered trademarks. ©2013..