



General Specifications

Power Requirement*	- VDC Regulated	6-18 VDC
Current Consumption	- Average	31mA
	- Peak	70mA
Card Read Range	- Metric	20mm - 40 mm
Operating Temperature	- USA	0.8" - 1.6"
	- Metric	-25°C to +65°C
Relative Humidity	- USA	-13°F to +149°F
	- % max	90%, operating non condensing
Reader Dimensions	- Metric	84.55mm (L) x 42.95mm (W) x 20.7mm (D)
	- USA	3.33" (L) x 1.69" (W) x 0.815" (D)
Status LED's	- Colour	Green, Red (ext control to Green)
Audible Tone		Internal & external buzzer control
Colour finish		Charcoal
Certifications		RCM Mark AU/NZ, FCC, CE
IP Rating		IP65
ROHS		Compliant

M2000

*At reader terminals

*Powerfully Versatile,
Elegantly Compact*

The Miniguard range of readers is stylish as well as functional with its low profile and slimline shape, allowing easy installation on door architraves or mullions where larger readers will not fit. It can be mounted directly on a metal door frame with no adverse effect to the reader's function. A universal back plate is also available for mounting on most international standard gang boxes.

Available in several models, the Miniguard for all security requirements large or small and offers a solution for all applications whether driven by budget or functionality.

Model Features

BM	Technology			Authentication Factors		Encode				Encryption			Sector Keys		13.56MHz Credential type and option				Output Protocol		Other									
	Mifare Classic	Mifare Plus	DESfire	Card	Biometric	Keypad	GSM/UID	Sector	Application	Random UID	Diversified Keys	Crypto 1	Mifare Plus	3 DES	AES (optional)	MiPASS 2	MiPASS 3	Customisable	ISO14443A	ISO14443B	Mifare 1K & 4K	Mifare Plus 2K & 4K	DESfire EV1 4K & 8K	Wiegand 32 BIT	Wiegand 26-199 BIT	Encrypted RS485*	Read / Write	Indoor / Outdoor	Tamper option	
BM681	✓			✓			✓													✓			✓							✓
BM682	✓			✓			✓	✓		✓	✓					✓			✓		✓		✓				✓	✓		✓
BM683	✓			✓			✓	✓		✓	✓							✓	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	✓
BM684		✓	✓	✓			✓	✓	✓	✓	✓		✓			✓			✓			✓	✓				✓	✓		✓
BM686	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

* Requires High Security Module (HSM) AES 128bit encryption

Contact BQT Solutions for more information or a discussion on custom options available, visit our website www.bqtsolutions.com for your nearest office.

[MAR2014] All specifications are subject to change without notice. Contact BQT Solutions to confirm. BQT Solution and miPASS are registered trademarks. ©2014.