



General Specifications

Power Requirement*	- VDC regulated	7-18 VDC
Current Consumption	- Average	30 mA
	(at 12VDC) - Peak	80 mA
Card Read Range	- Metric	20mm - 40 mm
	- USA	0.8" - 1.6"
Operating Temperature	- Metric	-25°C to +65°C
	- USA	-13°F to +149°F
Relative Humidity	- % max	90%, operating non condensing
Reader Dimensions	- Metric	119mm(H) x 40mm(W) x 24mm(D)
	- USA	4.69" (L) x 1.58" (W) x 0.95" (D)
Status LED's	- Colour	Green, Red (ext control to Green)
Audible Tone		Internal & external buzzer control
Colour finish		Charcoal
Certifications		RCM Mark AU/NZ, FCC, CE
IP Rating		IP65
ROHS		Compliant

M2000

* At Reader terminals

Seamless Migration

Slimline style, engineered for tough environments and seamless migrations.

The BT950 Series of readers are stylish as well as functional with its compact, low profile and slimline shape, allowing easy installation on door architraves or mullions where larger readers will not fit. It can be mounted directly on a metal door frame with no adverse effect to the reader's function.

Available in several models, including the dual technology BT951, the BT950 is the perfect migration reader and caters for all security requirements large or small, offering a solution for all applications whether economy or functionality are the driving considerations.

Model Features

Model	Technology			Authentication Factors			Encode				Encryption			Sector Keys			13.56MHz Credential type and option				Output Protocol		Other								
	125kHz Prox #	Mifare Classic	Mifare Plus	DESfire	Card	Biometric	Keypad	CSN/UID	Sector	Application	Random UID	Diversified keys	Crypto 1	Mifare Plus	3 DES	AES (optional)	MiPASS 2	MiPASS 3	Customisable	ISO14443A	ISO14443B	Mifare 1K & 4K	Mifare Plus 2K & 4K	DESfire EV1 4K & 8K	Wiegand 32 BIT	Wiegand 26-199 BIT	Encrypted RS485 *	Read / Write	Indoor / Outdoor	Tamper option	
BT950 -2	✓			✓				✓	✓		✓	✓				✓				✓	✓			✓			✓	✓		✓	
BT950 -3	✓			✓				✓	✓		✓	✓						✓	✓		✓	✓			✓	✓	✓	✓	✓	✓	✓
BT950 -4				✓	✓			✓	✓	✓	✓	✓		✓			✓			✓	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓
BT950 -6	✓	✓	✓	✓				✓	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓

125kHz Prox reads CSN but by its very nature has no encryption.

* Requires High Security Module (HSM) AES 128bit encryption.

Contact BQT Solutions for more information or a discussion on custom options available, visit our website www.bqtsolutions.com for your nearest office.

[MAR2014] All specifications are subject to change without notice. Contact BQT Solutions to confirm. BQT Solution and miPASS are registered trademarks. ©2014.