BT853



RFID READER DATASHEET 23.06.21

PRODUCT

The BT853 is a two-factor wall mount MIFARE® smart card reader with keypad and LCD display to provide direct feedback. They can be purchased preconfigured or customised to suit any requirement and are able to integrate seamlessly with existing systems and facilitate migrating to higher security technology.



MODEL FEATURES

		BT853-1	BT853-2	BT853-3	BT853-4	BT853-5	BT853-6
Technology	125kHz						
	MIFARE Classic®						
	MIFARE Plus®						
	MIFARE® DESFire®						
Factors	Card						
	Keypad						
	Biometric						
Encryption	CSN/UID						
	Crypto1						
	3DES						
	AES						
Keys	Diversified Key						
	Custom Key						
Output	Wiegand 32-bit						
	Wiegand 26-bit to 199-bit						
	Encrypted RS485						

SPECIFICATIONS

- Voltage at Reader 8VDC to 16VDC
- Current Usage Average: 180mA Peak: 240mA
- Card Read Range 20mm to 40mm (0.8" to 1.6")
- Operating Temperature
 -25°C to +65°C (-13°F to +149°F)
- Relative Humidity (% max)
 90%, operating non condensing
- Reader Dimensions 157mm (6.18") X 97mm (3.82") X 50mm (1.97")
- Materials
 Reader Body: ABS Plastic
 Colour Finish: Charcoal
 Mounting Bracket: Stainless
- Feedback
 Green/Red LED, with external control
 Buzzer, with external control
 Tamper detection, optional output

Keypad
 16 button illuminated, PIN on Card (PoC), 8-bit COTAG or

custom

- LCD Display
 8x20 characters,
 monochramatic, read/access
 messaging or custom in RS485
 mode
 - Credential Options
 ISO14443A, MIFARE Classic®
 1K/4K, MIFARE Plus® X 2K/4K,
 MIFARE® DESFire® EV1 4K/8K,
 MIFARE® DESFire® EV2 4K/8K,
 MIFARE® DESFire® EV3 4K/8K
- Compliance and Certification FCC, CE, UKCA, RCM, RoHS, IP65
- Reader Variants

 BT853-1 CSN Reader

 BT853-2 miPASS2 Reader

 BT853-3 Custom MIFARE

 Classic Reader

 BT853-4 miPASS3 Reader

 BT853-5 miPASS4 Reader


 BT853-6 Custom MIFARE

 DESFire Reader

DIAGRAM

DIAGRAMS ARE NOT TO SCALE. MEASUREMENTS ARE IN MILLIMETERS (MM).

Steel





CONTACT SALES@BQTSOLUTIONS.COM TO BE PUT IN TOUCH WITH YOUR LOCAL REPRESENTATIVE.

WWW.BQTSOLUTIONS.COM