

BIOMETRIC READER DATASHEET

23.06.21

PRODUCT

The BioX is a two-factor fingerprint biometric and MIFARE® smart card reader able to integrate seamlessly with existing systems. Can be configured as 'template on card' or for complete control, managed with miPASS Access software.



MODEL FEATURES


		BioX-1	BioX-2	BioX-3	BioX-4	BioX-5	BioX-6
Technology	125kHz						
	MIFARE Classic®	●	●	●			
	MIFARE Plus®						●
	MIFARE® DESFire®				●	●	●
Factors	Card	●	●	●	●	●	●
	Keypad						
	Biometric	●	●	●	●	●	●
Encryption	CSN/UID	●	●	●	●		●
	Crypto1		●	●			●
	3DES				●		●
	AES					●	●
Keys	Diversified Key		●		●	●	●
	Custom Key			●			●
Output	Wiegand 32-bit	●	●	●	●	●	●
	Wiegand 26-bit to 199-bit			●			●
	Encrypted RS485			●		●	●

SPECIFICATIONS

- **Voltage at Reader**
8VDC to 16VDC
- **Current Usage**
Average: 280mA
Peak: 350mA
- **Card Read Range**
20mm to 40mm (0.8" to 1.6")
- **Operating Temperature**
-10°C to +50°C (+14°F to +122°F)
- **Relative Humidity (% max)**
90%, operating non condensing
- **Reader Dimensions**
190mm (7.48") X 120mm (4.72")
X 60mm (2.36")
- **Materials**
Reader Body: ABS Plastic
Colour Finish: Charcoal
Mounting Bracket: Stainless Steel
- **Feedback**
Green/Red/Blue LED, with external control
Buzzer, with external control
- **Sensor**
Optical fingerprint sensor
- **Credential Options**
ISO14443A, MIFARE Classic® 1K/4K, MIFARE Plus® X 2K/4K, MIFARE® DESFire® EV1 4K/8K, MIFARE® DESFire® EV2 4K/8K, MIFARE® DESFire® EV3 4K/8K
- **Compliance and Certification**
FCC, CE, UKCA, RCM, RoHS, IP65
- **Reader Variants**
BioX-1 – CSN Reader
BioX-2 – miPASS2 Reader
BioX-3 – Custom MIFARE Classic Reader
BioX-4 – miPASS3 Reader
BioX-5 – miPASS4 Reader
BioX-6 – Custom MIFARE DESFire Reader

DIAGRAM

DIAGRAMS ARE NOT TO SCALE. MEASUREMENTS ARE IN MILLIMETERS (MM).



CONTACT SALES@BQTSOLUTIONS.COM TO BE PUT IN TOUCH WITH YOUR LOCAL REPRESENTATIVE.

WWW.BQTSOLUTIONS.COM