BT817



RFID READER DATASHEET 23.06.21

PRODUCT

The BT817 is a two-factor wall mount MIFARE® smart card reader with keypad that can be purchased preconfigured or customised to suit any requirement. Able to integrate seamlessly with existing systems and facilitate migrating to higher security technology.



MODEL FEATURES

		BT817-1	BT817-2	BT817-3	BT817-4	BT817-5	BT817-6
Technology	125kHz						
	MIFARE Classic®						
	MIFARE Plus®						
	MIFARE® DESFire®						
Factors	Card						
	Keypad						
	Biometric						
Encryption	CSN/UID						
	Crypto1						
	3DES						
	AES						
Keys	Diversified Key						
	Custom Key						
Output	Wiegand 32-bit						
	Wiegand 26-bit to 199-bit						
	Encrypted RS485						


SPECIFICATIONS

- Voltage at Reader 8VDC to 16VDC
- Current Usage Average: 90mA Peak: 190mA
- Card Read Range 20mm to 40mm (0.8" to 1.6")
- Operating Temperature -25°C to +65°C (-13°F to +149°F)
- Relative Humidity (% max) 90%, operating non condensing
- Reader Dimensions 90mm (3.54") X 90mm (3.54") X 28mm (1.10")
- Materials Reader / Shroud Body: ABS Plastic Colour Finish: Charcoal
- Feedback Green/Red LED, with external control Buzzer, with external control Tamper detection, optional output

- Keypad 12 button illuminated, PIN on Card (PoC), 8-bit COTAG or custom
- Credential Options ISO14443A, MIFARE Classic® 1K/4K, MIFARE Plus® X 2K/4K, MIFARE® DESFire® EV1 4K/8K, MIFARE® DESFire® EV2 4K/8K, MIFARE® DESFire® EV3 4K/8K
- Compliance and Certification FCC, CE, UKCA, RCM, RoHS, IP65
- Reader Variants BT817-1 - CSN Reader BT817-2 - miPASS2 Reader BT817-3 - Custom MIFARE Classic Reader BT817-4 - miPASS3 Reader BT817-5 - miPASS4 Reader BT817-6 - Custom MIFARE **DESFire Reader**
- Accessories B4023G000000 - BT817 Backbox B4033G000000 - BT817 Tamper Plate B4101G000000 - BT817 Replacement Shroud

DIAGRAM

DIAGRAMS ARE NOT TO SCALE. MEASUREMENTS ARE IN MILLIMETERS (MM).





CONTACT SALES@BQTSOLUTIONS.COM TO BE PUT IN TOUCH WITH YOUR LOCAL REPRESENTATIVE.

WWW.BQTSOLUTIONS.COM